PAN CONNECTORS

Technology from UK

To connect toilets with horizontal and Vertical outlets to standard SWR pipework, Ashirvad has introduced a range of products that are plumber friendly in nature, made of flexible plastic, the connectors tolerate movement, are leak proof (with multiple fins) and can connect different pipe materials.

APCS2 - Straight - HSN CODE: 39172390

SPIGOT	SWR	Part No.	Std. Pkg.	MRP` Inc. of all Taxes/pc
9.7 - 10.8 cm	9.9 - 10.5 cm	50013426	50	441

APC02 - 1.8 cm Offset - HSN CODE: 39172390

SPIGOT 9.7 - 10.8 cm	SWR 9.9 - 10.5 cm	50013427	45	471
-----------------------------	-----------------------------	----------	----	-----

APC04 - 4.0 cm Offset - HSN CODE: 39172390



APCC2 - Collapsible - HSN CODE: 39172390





The straight connector (APCS2) is used when the spigot outlet on the WC is in line with the SWR pipework system.

WC Inlet rubber bush / Washer



Specifications for Pan Connectors

- · Flexible and made in plastic
- WC load bearing
- Secure fit on WC side
- Connects different materials
- Multiple fins to ensure water tight fit on SWR side
- Individually packed
- · With Lubricant



12.5 x 11.0 cm

The flexible connector (APCC2) is extendable from 22.5 to 55.0 cm and is very useful when the SWR pipework is at a significant distance from the WC spigot outlet or if it is in a vertical position.



12.5 x 11.0 cm

The two ranges of offset connectors (APCO2 and APCO4) are useful if there is a mismatch between the centres of the spigot on the WC and the SWR pipework. Offsets of up to 4.0 cm can be catered to, by these two WC pan connectors.









